

STANDARD DAMPERS

ALL PARTS HAVE LIP SEALS & BLACK NITRIDE SHAFT (CHROME AVAILABLE UPON REQUEST)									DAMPENING VALUE
			<i>PS</i> PLASTIC 10mm BS M6 THD	<i>PC</i> PLASTIC 10mm BS M6 THD	<i>SB or ZB</i> STEEL or ZINC THRU HOLE M6 THD	<i>SC</i> STEEL 10mm BS M6 THD	<i>ST</i> STEEL 10mm BS M6 THD	<i>TH6</i> M6 THD <i>ONLY</i>	RATE
ATLAS INDUSTRIAL P/N	ØSHAFT X ØBODY (mm)	STROKE (In)	EXTENDED LENGTH (In)	EXTENDED LENGTH (In)	EXTENDED LENGTH (In)	EXTENDED LENGTH (In)	EXTENDED LENGTH (In)	EXTENDED LENGTH (In)	LIGHT MEDIUM HEAVY
AD15x-200x	6 x 15	2.00	7.89	7.89	7.89	7.89	7.89	6.47	L, M or H
AD15x-300x	6 x 15	3.00	10.02	10.02	10.02	10.02	10.02	8.60	L, M or H
AD15x-400x	6 x 15	4.00	12.50	12.50	12.50	12.50	12.50	11.08	L, M or H
AD15x-500x	6 x 15	5.00	15.02	15.02	15.02	15.02	15.02	13.60	L, M or H
AD18x-200x	8 x 18	2.00	7.89	7.89	7.89	7.89	7.89	6.47	L, M or H
AD18x-300x	8 x 18	3.00	10.02	10.02	10.02	10.02	10.02	8.60	L, M or H
AD18x-400x	8 x 18	4.00	12.50	12.50	12.50	12.50	12.50	11.08	L, M or H
AD18x-500x	8 x 18	5.00	15.02	15.02	15.02	15.02	15.02	13.60	L, M or H
AD22x-400x	8 x 22	4.00	12.24	12.24	12.24	12.24	12.24	10.83	L, M or H
AD22x-500x	8 x 22	5.00	14.49	14.49	14.49	14.49	14.49	13.07	L, M or H
AD22x-600x	8 x 22	6.00	17.01	17.01	17.01	17.01	17.01	15.59	L, M or H
AD22x-700x	8 x 22	7.00	19.65	19.65	19.65	19.65	19.65	18.23	L, M or H

PART NUMBERING EXAMPLE: AD15E-200M-SB

AD	STANDARD DAMPER
15	6x15 DESIGN
E	EXTENSION DAMPED ONLY
200	2.00" STROKE
M	MEDIUM DAMPED
SB	STEEL BLADE CONNECTOR

